

# Atmospheric & Space Technology Research Associates LLC www.astraspace.net











# Ensemble Assimilation Using First-Principles Models: A Tool for Three-Day Space Weather Forecasts

Space Weather Workshop, 2015

April 16<sup>th</sup>, 2015

G. Crowley<sup>1</sup>, M. Pilinski<sup>1</sup>, J. Wolfe<sup>1</sup>, T. Fuller-Rowell<sup>2</sup>, T. Matsuo<sup>2</sup>, S. Solomon<sup>3</sup>, L. Qian<sup>3</sup>, J. Thayer<sup>4</sup>, M. Codrescu<sup>5</sup>

<sup>1</sup>ASTRA LLC., <sup>2</sup>CIRES. <sup>3</sup>UCAR, <sup>4</sup>U. of Colorado, <sup>5</sup>NOAA

# ASTRA: Space Weather Focus

Technology Applications

Bringing It All Together




Modeling

**Physics-Based Modeling** 

**Real-Time Specification** of Ionosphere/ **Thermosphere** 

(TIMEGCM)




Data **Assimilation** 

**High-latitude Electrodynamics** 

> Global Ionosphere

**Thermospheric Neutral Density** 




Data **Services** 

**Space Based Data** 

**Ground Based Data** 

**Forensic Space** Weather **Analysis** 

**Space weather Phone Apps** 



**Ground-based** Instrument **Development** 

**GPS-based Space Weather Monitor** 

E-fields and **Magnetometers** 

> **Low Power** Ionospheric Sounder

**HF TID Mapper** 

**Lidar Systems** 

Space **Systems** 

**CubeSat Missions** 

**NSF: DICE & LAICE** 

**AF: DIME, SIPS & TSS** 

**NASA: SORTIE & MiRaTa** 

**Plug-N-Play Avionics** 

**CubeSat Instruments** 

**Scanning UV Photometer** 

E-field Double Probe

**RF Waves & Sounder** 

**Wind Profiler** 

**GPS-based Space Weather Monitor** 


Magnetometer & **Langmuir Probe** 

**Satellite Aerodynamics** 

ASTRA • www.astraspace.net 303-993-8039 · solutions@astraspace.net

© 2015 Atmospheric & Space Technology Research Associates, LLC













Figure 1c: Typical profiles of neutral atmospheric temperature




### Who cares about satellite drag?




Bringing It All Together

Satellite drag errors degrade capability to:

- Maintain accurate catalog of all space objects
- Predict and avoid space collisions
- Predict satellite reentry time & location








Bringing It All Together

### **Direct Atmospheric Impacts**

- Density = f(Temp, Composition)
- Winds

# **Indirect Atmospheric Impacts (through force coefficient)**

- Composition
- Temperature
- Winds
- Mean-Free Path




$$a_{D} = -\frac{1}{2} \frac{C_{D}(T_{a}, V, \lambda, n_{O}, n_{N_{2}}, ..., n_{H})A}{m} \rho(T_{a}, n_{N_{2}}, ..., n_{H})V^{2}$$

### **Density Perturbations at 400 km**

❖Science❖ Technology❖ Applications



Bringing It All Together




### **ADAM Overview and Benefits**

Technology Applications

Bringing It All Together



### **Resident Space Objects (LEO)**



satellite drag and density observations

- Orbit observations
- GPS
- Accelerometers
- · 0/N2
- Mass Spectrometer

conjunction analysis

#### Results

- Improved satellite orbit nowcast and 72h forecast
- Improvements over HASDM and JB08
- Up to three-fold improvement during storms and solar minimum
- · Densities, winds, and composition outputs
- Covers altitudes from 30 km to 1500 km
- Improved performance during geomagnetic storms

**A**tmospheric

Density

Assimilation

**Output** information


orbit prediction and

determination tools

feeds into existing

Model

#### **ADAM Architecture**



### **Super-Ensemble Approach**





	Requirement	Goal
Nowcast	Outperform JB08	Outperform HASDM
		(Jacchia '70, with 60-90 objects)
	JB08: 7-18% at 200-800km	HASDM: 6-10% at 200-800km
72h Forecast	Outperform JB08 in forecast mode	Outperform HASDM in forecast mode

### **ADAM Overview and Benefits**


Science

TechnologyApplications

Bringing It All Together







satellite drag and density observations

- Orbit observations
- GPS
- Accelerometers
- · 0/N2
- Mass Spectrometer

conjunction analysis **A**tmospheric

Density

Assimilation

**Output** information


orbit prediction and

determination tools

feeds into existing

Model

#### **ADAM Architecture**



#### Results

- Improved satellite orbit nowcast and 72h forecast
- Improvements over HASDM and JB08
- Up to three-fold improvement during storms and solar minimum
- Densities, winds, and composition outputs
- Covers altitudes from 30 km to 1500 km
- Improved performance during geomagnetic storms


Super-Ensemble Approach



Image credit: TerraMetrics, Google



# <u>Important Inputs to the</u> <u>Thermosphere – Ionosphere System</u>




## **ADAM top level design**


❖Science❖ Technology❖ Applications



Bringing It All Together









G. Crowley, M. Pilinski, J. Wolfe

physics members (based on 40-day trailing average)







Improvements in neutral density when high-latitude electric fields are specified using assimilated electric fields



- Multiple model (super-ensemble) approach
- Dynamically tuned models result in optimum background atmospheric state
- Data Assimilation
- Graceful degradation in case of input-stream or model interruption
- Inclusion of TIME-GCM allows for specification of densities in the re-entry regime, down to 30km
- Inclusion of Helium in several models allows for drag computation up to 1500km

### **Architecture for Realtime Ensemble Runs**

TechnologyApplications




Implemented and tested with:

TIE, TIME, CTIPe

 Ensembles executed in parallel on multiple cores

> Unified Input Database

- Schedule based rather than event based operation
  - Leads to graceful degradation in event of data-loss



time?


G. Crowley, M. Pilinski, J. Won

# **Assimilation**


## **Optimal Interpolation (OI)**

❖Science
❖ Technology

Applications








## ADAM top level design

Science Technology Applications




Bringing It All Together



# **Realtime Ensemble Tests**

❖ Science
 ❖ Technology
 ❖ Applications
 Bringing It All Together








- TLE's are being used as a stand in for orbital arcs analysis
  - Cadence and arc length is a conservative stand-in for the special-perturbations approach available operationally to the customer
  - Will transition to 6-hour arcs from special perturbations analysis in Phase III

- Temporary Drawbacks
  - Lower signal-to-noise
  - Latency (~1 day)








### **Assimilated Data Types**

Data Type	Assimilation Time Span	Notes
Orbit Average Drag i.e. Calspheres, DANDE, POPACS	6-72 h	Infer observed energy dissipation rate (EDR) from general perturbations (TLEs) or special perturbations (high task tracking data). Select 30-90 objects with stable ballistic coefficients.
Orbit Average Densities	24 hours	Already processed high-task tracking data
Orbit Resolved Drag: GPS	15-30 min	Observed EDR from special perturbations and GPS measurements
Orbit Resolved Drag: accelerometers (Swarm)	15 min	Observed acceleration at 10-45 sec cadence (in-track and cross-track), binned to 15 min
O/N2 (GOLD, DMSP-SSUSI)	30 min	Dayside disk composition
Mass Spectrometer	10-30 sec	In-situ day and night composition

Technology

Applications











**VANGUARD II** 

DFH-I

**EXPLORER VII** 









**DANDE** 

**POPACS 1, 2, 3** 

**RIGIDSPHERE 2** 

AZUR (GRS A)








PAM-D (left), SL-3 (center), SL-8 (right) rocket body outlines, shown to scale

190 – 900 km altitude, ±90° latitude coverage



- New state-of-the-art assimilative model of the thermosphere is being developed
- Include many of the lessons learned from NADIR MURI project (funded by AFOSR)
- 1<sup>st</sup> year into a 2-yr project
- Expected to meet AF goals and requirements for specifying satellite drag
- Future plans to make outputs commercially available to civilian customers



# ❖ Technology ❖ Applications Bringing It All Together


Science



Relative importance of various scales

- Large scale perturbations can be misrepresented in empirical models
- It takes long-wavelength perturbations to cause significant position errors
- 3U sun-pointing CubeSat  $\frac{C_D A}{m} \approx 0.02 \quad \left[\text{m}^2/\text{kg}\right]$
- 100m errors are considered "significant" by USAF at 400 km altitude [Anderson et al. 2008]





❖ Technology
❖ Applications
Bringing It All Together

Science




Relative importance of various scales

What physical processes are important?

- Large scale storm structures
- Seasonal variability
- Density cell
- Cusp enhancement
- Non-hydrostatic effects

### 24 Hour Orbital In-Track Error at 400km Circular Orbit



❖ Technology❖ Applications

Science




Bringing It All Together

Relative importance of various scales

### What physical processes are important?

- Large scale storm structures
- Seasonal variability
- Density cell
- Cusp enhancement
- Non-hydrostatic effects

### 24 Hour Orbital In-Track Error at 400km Circular Orbit



❖Science❖ Technology❖ Applications




Bringing It All Together

Relative importance of various scales

### What physical processes are important?

- Large scale storm structures
- Seasonal variability
- Density cell
- Cusp enhancement
- Non-hydrostatic effects

### 24 Hour Orbital In-Track Error at 400km Circular Orbit



Science Technology Applications




Relative importance of various scales **Bringing It All Together** 

### What physical processes are important?

- Large scale storm structures
- Seasonal variability
- Density cell
- **Cusp enhancement\***
- Non-hydrostatic effects

### 24 Hour Orbital In-Track Error at 400km **Circular Orbit**



<sup>\*</sup>not a persistent feature on these time scales

Science Technology Applications




**Bringing It All Together** 

### Relative importance of various scales

### What physical processes are important?

- Large scale storm structures
- Seasonal variability
- Density cell
- Cusp enhancement
- Non-hydrostatic effects\*

### 24 Hour Orbital In-Track Error at 400km **Circular Orbit**



<sup>\*</sup>not a persistent feature on these time scales